

Technical data

Art. no.	10886
Gauge	H0 / TT / N
PIN/Interface	6 pole, angled pins
According to NEM	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No 651
Cable	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
DCC	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
MM	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Load regulation	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
POM	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Only program
NMRA compatible	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Speed steps (14, 28, 128)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Max. motor current	1.0 A
Light and function outputs – of which outside interface	2, summary current: max. 0.2 A –
Max. decoder sum current	1.0 A
Short-circuit protection of all outputs	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Dimensions	12.9 x 9 x 3.4 mm
RailCom®	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Complies with ZIMO article	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Updatable	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Breaking section support	
Lenz ABC	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Märklin 72441/72442	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
ZIMO HLU	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Connection possibility for energy storage	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Standard sound (Steam-, Diesel-, Electric locomotives)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Loudspeaker	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No